



Ordering Information

Dura-Tile II & Dura-Tile Rolls™

| Item No. | Size | Weight |
|----------|-----------------|-----------------|
| 345S1212 | 12" x 12" | 2.3 lbs./sq.ft. |
| 345R0025 | 12" x 25" | 2.3 lbs./sq.ft. |
| 345C0000 | 12" x up to 25" | 2.3 lbs./sq.ft. |

Colored Dura-Tile II™

| Item No. | Size | Weight |
|----------|-----------|-----------------|
| 345S1212 | 12" x 12" | 2.3 lbs./sq.ft. |

Adhesive & Nosing

| Item No. | Description | Weight |
|----------|-----------------------|-----------------|
| 345A0001 | 1 gallon can adhesive | 9 lbs. ea. |
| 345B0000 | Beveled Nosing | 0.4 lbs./sq.ft. |

Dura-Tile II 95% Recycled Content

| Size | Rubber/Tire | Tires/Tile | 1 Tire |
|-----------|-------------|------------|----------|
| 12" x 12" | 2 lbs. | .07 | 15 Tiles |


1 Tire = 30 lbs.

Environmentally friendly, made from post consumer bias-ply tires. Attractive carpet-like surface provides a touch of luxury in areas of frequent foot traffic. Traps dirt, absorbs moisture, and protects floors. Easily maintained with vacuum cleaner or hose. Suitable for any entrance or as wall to wall floor covering. Meets Federal flammability regulations DOC FF 1-70. According to AMCIC Test, Dura-Tile exceeds the minimum char radius of 3" Average car, per 8 strips tested, .75" radius.

Material: Rubberized fabric strips with chenille-like surface cut from recycled tires bonded to non-flammable base.

Thickness: 3/8" (with +1/8 ~ 0")

Nosing (optional): Black beveled vinyl nosing for finished approaches on surface installation.



Standard Earthtone Red Tone Green Tone Blue Tone Charcoal Tone Brown Tone



DURABLE
CORPORATION
SINCE 1923

75 North Pleasant Street • Norwalk, OH 44857
800-537-1603 • Local 419-668-8138
Fax: 800-537-6287 • Local Fax 419-668-8068
www.durablecorp.com • sales@ durablecorp.com