

Environmentally friendly, made from post consumer bias-ply tires. Attractive carpet-like surface provides a touch of luxury in areas of frequent foot traffic. Traps dirt, absorbs moisture, and protects floors. Easily maintained with vacuum cleaner or hose. Suitable for any entrance or as wall to wall floor covering. Meets Federal flammability regulations DOC FF 1-70. According to AMCIC Test, Dura-Tile exceeds the minimum char radius of 3" Average car, per 8 strips tested, .75" radius.

Material: Rubberized fabric strips with chenillelike surface cut from recycled tires bonded to nonflammable base.

Thickness: 3/8" (with $+1/8 \sim 0$ ")

Nosing (optional:) Black beveled vinyl nosing for finished approaches on surface installation.



Standard

Earthtone



Tone





Blue

Tone



Charcoal Tone

Tone

Ordering Information

Dura-Tile & Dura-Tile RollsTM

Item No.	Size	Weight
345S1212	12" x 12"	2.3 lbs./sq.ft.
345R1225	12" x 25"	57.50/roll

Colored Dura-TileTM

Item No.	Size	Weight
345S1212*	12" x 12"	57.50/roll
*Use Color Codes	s: Red(RD), Blue(E	BL), Green(GN),
Brown(BN), Char	rcoal(CH)	

Adhesive & Nosing

Item No.	Description	Weight
345ADHSV	1 gallon can adhesive	9 lbs. ea.
345NOSE	Beveled Nosing	0.5 lbs./lin.ft.

Dura-Tile II 95% Recycled Content

Size	Rubber/Tile	Tires/Tile	1 Tire
12" x 12"	2 lbs.	.07	15 Tiles

1 Tire = 30 lbs.





Tone

75 North Pleasant Street • Norwalk, OH 44857 800-537-1603 • Local 419-668-8138 Fax: 800-537-6287 • Local Fax 419-668-8068 www.durablecorp.com • sales@durablecorp.com