



Diamond Tread mat surface provides dependable traction underfoot. Non-conductive compound material helps prevent electric shock from instruments, machinery or control panels. Conforms to OSHA requirements and is tested to meet ASTM D-178 requirements. Each roll is proof tested at the specified voltage over the entire surface. Also meets the optional requirements cited by ASTM for flame resistance, ozone resistance and oil resistance. Orders are billed according to actual yardage shipped and may vary up to 10%.

**Material:** Specially compounded material with corrugated surface

**Dielectric Test** 30,000 Volts AC. Each roll proof tested over entire surface at 20,000 volts AC.

**Voltage:** Recommended maximum use voltage 17,0000 volts AC.

**Thickness:** 1/4"

**Surface:** Diamond Tread

**Colors:**

**Full Rolls**

| Item No. | Size           | Weight (Lbs/Roll) |
|----------|----------------|-------------------|
| 752R24   | 24" x 25 yards | 225               |
| 752R36   | 36" x 25 yards | 382               |
| 752R48   | 48" x 25 yards | 510               |

**Cut Lengths**

| Item No. | Item No. | Weight (Lbs/Lin Yd) |
|----------|----------|---------------------|
| 752C24   | 24" wide | 10.2                |
| 752C36   | 36" wide | 15.3                |
| 752C48   | 48" wide | 20.4                |



Black



Black w/Yellow Border  
•Available in 3' wide only