# **Dura-Tile II**


## **Entrance Mat**



Environmentally friendly, made from post consumer bias-ply tires. Attractive carpet-like surface provides a touch of luxury in areas of frequent foot traffic. Traps dirt, absorbs moisture, and protects floors. Easily maintained with vacuum cleaner or hose. Suitable for any entrance or as wall to wall floor covering. Meets Federal flammability regulations DOC FF 1-70. According to AMCIC Test, Dura-Tile exceeds the minimum char radius of 3" Average car, per 8 strips tested, .75" radius.

**Material**: Rubberized fabric strips with chenillelike surface cut from recycled tires bonded to nonflammable base.

**Thickness:** 3/8" (with  $+1/8 \sim 0$ ") **Nosing (optional:)** Black beveled vinyl nosing for finished approaches on surface installation. **Colors:** 





## **Ordering Information**

<b>Dura-Tile II</b>	& Dura-Tile	<b>Rolls</b> <sup>TM</sup>
---------------------	-------------	----------------------------

Item No.	Size	Weight
345S1212	12" x 12"	2.3 lbs./sq.ft.
345R0025	12" x 25"	2.3 lbs./sq.ft.
345C0000	12" x up to 25'	2.3 lbs./sq.ft.

#### Colored Dura-Tile II<sup>TM</sup>

 Item No.
 Size

 345\$1212
 12" x 12"

2

Weight 2.3 lbs./sq.ft.

### Adhesive & Nosing

Item No.Description345A00011 gallon can adhesive345B0000Beveled Nosing0.

Weight 9 lbs. ea. 0.4 lbs./sq.ft.

Dura-Tile II					
95% Recycled Content					
Size	Rubber/Tile	Tires/Tile	1 Tire		
12" x 12"	2 lbs.	.07	15 Tiles		

1 Tire = 30 lbs.



75 North Pleasant Street • Norwalk, OH 44857 800-537-1603 • Local 419-668-8138 Fax: 800-537-6287 • Local Fax 419-668-8068 www.durablecorp.com • sales@durablecorp.com